

AI Health 2026

Heart-Rate-Based Work-Rest Scheduling in Construction

March 9, 2026

Tala Yunis, Dr. Issam Srour, Dr. Karim Zahed

Email: KZ28@aub.edu.lb



**Long,
Physically Demanding
Workday**



**Fatigue
Cycle**




**Injuries & Errors
Slower Productivity
Overtime & Schedule Pressure**

Literature – Measuring Fatigue In Construction



Fatigue is often assessed using both **subjective** ratings and **objective** signals.*^[1]



Fatigue scales vary widely across workers.^[2]



Repeated reporting can be **disruptive** and **impractical** during construction tasks.^[3]




→ These limitations motivate continuous, non-intrusive monitoring using wearable sensors

Research Gaps

Recent studies have explored wearable sensors for **work–rest** allocation and **micro-breaks**.


- Many frameworks rely on **simplified or simulated scenarios**.
- Limited studies use **continuous physiological data** from **real construction sites**.

→ Need for a practical framework that translates wearable physiology into work–rest scheduling decisions.



No practical physiology-guided work–rest scheduling framework for construction sites

Proposed Framework



- Monitor workers' **heart rate** on **active** construction sites using **wearable** devices.
- Trigger and size rest breaks based on percentage **heart-rate reserve** (%HRR).
- **Optimize** break allocation using a model that **maximizes physiological recovery**.

Methodology

Field & Wearable Data

Physiological Metric

Work–Rest Scheduling

Sites & Workers

- **33** workers
- **3 active construction sites** in Beirut.
- Residential and institutional projects.
- Mixed trades and skills.

On-Site Data Collection

- **Full-shift monitoring** (Mon–Sat) during working hours.
- Continuous physiological monitoring on-site.

Wearable Device & Signals

- Fitbit Inspire 3 (wrist); minute-level HR.
- **Researcher synced** data, which is uploaded to an **AWS**.

Heart Rate Reserve (%HRR)

$$\%HRR = \frac{HR_{Work} - HR_{Resting}}{HR_{Maximum} - HR_{Resting}} \times 100\%$$

- $\%HRR$ expresses current HR relative to resting and maximal HR [4]
- $\%HRR$ is used instead of raw HR because it accounts for **differences** in resting and maximum HR, making **strain comparable across workers**.


Rest Allowance (RA)

$$RA = \max\left(0, \frac{HR_{Work} - HR_{Endurance}}{HR_{Maximum} - HR_{Resting}}\right) \times \text{Work Duration}$$

- Time spent at high $\%HRR$ indicates physiological strain [5]
- A rest allowance rule converts accumulated strain into required break time.
- During a break, heart rate decreases toward resting levels.

Identifying Candidate Breaks

- RA is computed on a sliding **60-minute window** (1-minute step).
- Whenever $RA > 0$, a candidate break is created with **duration equal to the RA output**.
- For each candidate break, **$\Delta\%HRR$ (benefit)** is computed:
 - $\Delta\%HRR = (\%HRR \text{ without break}) - (\%HRR \text{ with break})$,
 - expressed as a **minute-weighted average reduction**.



Optimization of Break Selection

Candidate breaks are generated from the **rest allowance** rule, but only a **limited** number can be scheduled.

Constraints


- Daily rest budget per worker (e.g., 30 minutes excluding lunch)
- Minimum spacing between breaks
- Breaks must occur within the working hours

Objective

- The optimization model selects breaks that **maximize** physiological **recovery**.
- **Recovery** benefit is measured using **$\Delta\%HRR$** (marginal reduction in physiological strain).

Takeaway


The model prioritizes breaks that provide the largest recovery benefit per minute of rest.




Results

Physiological Workload Patterns

- Mean worker age: **29 years**
- Worker mean workload ranged from **~17% to 41% HRR** [Substantial variability between workers]
- **92% of worker-days triggered at least one candidate break**




Effect of Optimized Break Scheduling



- Candidate breaks typically required **5–15 minutes** of rest per day
- Without limits, average required rest \approx **40 minutes** per worker-day
- As shown in the figure, with a **30-minute daily cap**, optimized breaks **reduced the share of workday minutes with %HRR \geq 40%** while keeping **average workload nearly unchanged**

Conclusion

Limitations and Future Work



Incorporate **additional sensors** and contextual data
Test **real-world** implementation of **optimized** schedules

Key Findings

- Wearable **minute-level heart-rate data** can be used to monitor physiological workload on active construction sites.
- A **rest-allowance rule** converts physiological strain (%HRR) into candidate recovery breaks.
- An **optimization model** selects breaks that maximize physiological recovery under practical scheduling constraints.
 - Targeted rest breaks **reduce high-strain exposure without increasing overall downtime.**
 - **We could integrate AI into this scheduling approach to learn how and when workers need breaks.**

Thank You

References

1. Zong, H., Yi, W., Chan, A. P. C., Yang, H., Wu, P., & Xiao, B. (2025). Developing a Fatigue Model for Construction Workers: An Interpretable Machine Learning Approach. *Journal of Management in Engineering*, 41(4), 04025025. <https://doi.org/10.1061/JMENEA.MEENG-6662>.
2. Umer, W., Yu, Y., Fordjour Antwi Afari, M., Anwer, S., & Jamal, A. (2023). Towards automated physical fatigue monitoring and prediction among construction workers using physiological signals: An on-site study. *Safety Science*, 166, 106242. <https://doi.org/10.1016/j.ssci.2023.106242>.
3. Bangaru, S. S., Wang, C., & Aghazadeh, F. (2022). Automated and Continuous Fatigue Monitoring in Construction Workers Using Forearm EMG and IMU Wearable Sensors and Recurrent Neural Network. *Sensors (Basel, Switzerland)*, 22(24), 9729. <https://doi.org/10.3390/s22249729>.
4. Rodahl, K. (1989). *Physiology Of Work*. CRC Press.
5. Price, A. D. F. (1990). Calculating relaxation allowances for construction operatives — Part 2: Local muscle fatigue. *Applied Ergonomics*, 21(4), 318–324. [https://doi.org/10.1016/0003-6870\(90\)90203-A](https://doi.org/10.1016/0003-6870(90)90203-A)